


SAE 140130



1404R

Restrictor MP x NPSM Adapter

Female Pipe Swivels (NPSM)

1404R-①-②-③ ①-MP ②-FPX ③-Orifice	① Male NPTF	② Female NPSM Swivel	③ Orifice	C Body Hex	C1 Nut Hex	L (Ref. *) Length	Operating Pressure
1404R-02-02-.000	1/8 - 27	1/8 - 27	Blank	9/16	9/16	1.04	5,000
1404R-02-02-.032	1/8 - 27	1/8 - 27	1/32	9/16	9/16	1.04	5,000
1404R-02-02-.062	1/8 - 27	1/8 - 27	1/16	9/16	9/16	1.04	5,000
1404R-04-04-.000	1/4 - 18	1/4 - 18	Blank	11/16	11/16	1.49	5,000
1404R-04-04-.032	1/4 - 18	1/4 - 18	1/32	11/16	11/16	1.49	5,000
1404R-04-04-.062	1/4 - 18	1/4 - 18	1/16	11/16	11/16	1.49	5,000
1404R-06-06-.000	3/8 - 18	3/8 - 18	Blank	7/8	7/8	1.60	4,000
1404R-06-06-.032	3/8 - 18	3/8 - 18	1/32	7/8	7/8	1.60	4,000
1404R-06-06-.062	3/8 - 18	3/8 - 18	1/16	7/8	7/8	1.60	4,000
1404R-06-08-.000	3/8 - 18	1/2 - 14	Blank	7/8	1"	1.66	3,500
1404R-06-08-.032	3/8 - 18	1/2 - 14	1/32	7/8	1"	1.66	3,500
1404R-06-08-.062	3/8 - 18	1/2 - 14	1/16	7/8	1"	1.66	3,500
1404R-08-08-.000	1/2 - 14	1/2 - 14	Blank	1"	1"	1.92	3,500
1404R-08-08-.032	1/2 - 14	1/2 - 14	1/32	1"	1"	1.92	3,500
1404R-08-08-.062	1/2 - 14	1/2 - 14	1/16	1"	1"	1.92	3,500
1404R-12-12-.000	3/4 - 14	3/4 - 14	Blank	1 1/4	1 1/4	2.08	2,200
1404R-12-12-.032	3/4 - 14	3/4 - 14	1/32	1 1/4	1 1/4	2.08	2,200
1404R-12-12-.062	3/4 - 14	3/4 - 14	1/16	1 1/4	1 1/4	2.08	2,200

*Reference length only

4:1 Safety Factor

③ We can also drill the blank restrictor (.000) to your specifications.

③ More **RESTRICTOR** fittings

1404R (pg. 43)	6400R (pg. 134)
1501R (pg. 47)	6801R (pg. 157)
2404R (pg. 70)	6900R (pg. 167)
2406R (pg. 73)	6901R (pg. 169)
5405R (pg. 114)	6902R (pg. 171)