


SAE 070601

Ref. Aeroquip 2041 (-1)
 Ref. Parker WTX / 0353
 Ref. Weatherhead 5325




2700
Bulkhead Union

2700-①-② ①-MJ ②-BH	Tube O.D.	① Male JIC	② Bulkhead Male JIC	C Hex	I Assembled	L Length	Ø W Diameter	Operating Pressure
2700-02-02	1/8	5/16 - 24	5/16 - 24	9/16	1.11	1.87	0.31	7,500
2700-03-03	3/16	3/8 - 24	3/8 - 24	5/8	1.11	1.90	0.38	7,500
2700-04-04	1/4	7/16 - 20	7/16 - 20	11/16	1.20	2.07	0.44	7,500
2700-05-05	5/16	1/2 - 20	1/2 - 20	3/4	1.20	2.07	0.50	6,000
2700-06-06	3/8	9/16 - 18	9/16 - 18	13/16	1.28	2.18	0.56	6,000
2700-08-08	1/2	3/4 - 16	3/4 - 16	1"	1.44	2.44	0.75	6,000
2700-10-10	5/8	7/8 - 14	7/8 - 14	1 1/8	1.58	2.74	0.88	5,000
2700-12-12	3/4	1 1/16 - 12	1 1/16 - 12	1 3/8	1.75	3.09	1.06	5,000
2700-14-14	7/8	1 3/16 - 12	1 3/16 - 12	1 1/2	1.75	3.12	1.19	5,000
2700-16-16	1"	1 5/16 - 12	1 5/16 - 12	1 5/8	1.75	3.14	1.31	4,000
2700-20-20	1 1/4	1 5/8 - 12	1 5/8 - 12	1 7/8	1.80	3.31	1.63	4,000
2700-24-24	1 1/2	1 7/8 - 12	1 7/8 - 12	2 1/8	1.81	3.52	1.88	3,000
2700-32-32	2"	2 1/2 - 12	2 1/2 - 12	2 3/4	2.09	4.20	2.50	2,000

4:1 Safety Factor

SAE 070118

Ref. Aeroquip 210212
 Ref. Parker WLN / 53N
 Ref. Weatherhead 5924



306
Bulkhead Locknut

306-① Part No.	① Tube Thread	C Hex	T Thickness
306-02	5/16 - 24	9/16	0.22
306-03	3/8 - 24	5/8	0.22
306-04	7/16 - 20	11/16	0.28
306-05	1/2 - 20	3/4	0.28
306-06	9/16 - 18	13/16	0.27
306-08	3/4 - 16	1"	0.31
306-10	7/8 - 14	1 1/8	0.36
306-12	1 1/16 - 12	1 3/8	0.41
306-14	1 3/16 - 12	1 1/2	0.41
306-16	1 5/16 - 12	1 5/8	0.41
306-20 ①	1 5/8 - 12	1 7/8	0.41
306-24 ①	1 7/8 - 12	2 1/8	0.41
306-32 ①	2 1/2 - 12	2 3/4	0.41

① The Bulkhead Locknut (306) and the Adjustable Locknut (306N) are the exact same dimensions for sizes -20, -24, & -32.