


SAE 100R2

Ref. BRN 3051



5502C

Compact Street "Dot" Ell
Male x Female Pipe


5502C-①-② ①-MP ②-FP	① Male NPT	② Female NPT	N Length	Y Flats	Operating Pressure
5502C-02-02	1/8 - 27	1/8 - 27	0.78	5/8	5,000
5502C-04-04	1/4 - 18	1/4 - 18	1.09	7/8	5,000
5502C-06-04	3/8 - 18	1/4 - 18	1.22	3/4	4,000
5502C-06-06	3/8 - 18	3/8 - 18	1.12	7/8	4,000
5502C-08-06	1/2 - 14	3/8 - 18	1.19	7/8	3,500
5502C-08-08 ①	1/2 - 14	1/2 - 14	2.00	1 1/8	3,500
5502C-12-12 ②	3/4 - 14	3/4 - 14	1.55	1 3/8	2,200

① NPTF threads. ② 303 stainless steel.

4:1 Safety Factor

SAE 140339

Ref. Aeroquip 2088
Ref. Parker CD45 / 3102
Ref. Weatherhead C3359



5503

Street Elbow
Male x Female Pipe

5503-①-② ①-MP ②-FP	① Male NPTF	② Female NPTF	N Length	N1 Length	Y Flats	Operating Pressure
5503-02-02-4	1/8 - 27	1/8 - 27	0.72	0.47	9/16	5,000
5503-04-04-4	1/4 - 18	1/4 - 18	1.05	0.63	3/4	5,000
5503-06-06-4	3/8 - 18	3/8 - 18	1.06	0.72	7/8	4,500
5503-08-08-4	1/2 - 14	1/2 - 14	1.34	0.91	1 1/16	3,000
5503-12-12-4	3/4 - 14	3/4 - 14	1.38	0.97	1 5/16	3,000
5503-16-16-4	1 - 11 1/2	1 - 11 1/2	1.72	1.12	1 5/8	1,800
5503-20-20-4	1 1/4 - 11 1/2	1 1/4 - 11 1/2	1.80	1.63	1 7/8	1,500
5503-24-24-4	1 1/2 - 11 1/2	1 1/2 - 11 1/2	1.80	1.63	1 7/8	1,500

4:1 Safety Factor

Pipe Thread information is on page 106–107.